



EFFICIENT EXCELLENT ENERGY++

HIGH EFFICIENCY
TOPCON
PV MODULE
Celestia



BIFACIAL PV MODULES N-TYPE 156 HALF CUT

605 – 630 W_p



16BB HALF - CUT CELL TECHNOLOGY

New circuit design, lower internal current, lower resistive losses, energy yield is higher.

LOWER THE RISK OF HOT SPOT

Special circuit design with a much lower hot spot temperature.

EXCELLENT QUALITY & ENHANCED RELIABILITY

More than 14+ years' experience of manufacturing and intensive 40+ quality tests above the IEC standard ensures reliable modules.

SUPER STRONG FRAME

Module certified to withstand extreme wind (2400 Pascal) and snow loads (5400 Pascal) with 18 microns anodization thickness.

EXCELLENT LOW LIGHT & ANTI - PID PERFORMANCE

Tested 3 times of IEC TS 62804.




SWELECT's solar modules meet global quality and safety standards, including IEC, UL, CAN and BIS.

Comprehensive Product & System Certificates*

- ✓ BIS Certified (IS 14286 & IS/IEC 61730 - 1&2)
- ✓ IEC 61215: Design qualification and type approval
- ✓ IEC 61730: Module safety qualification
- ✓ IEC TS 62804: Potential Induced Degradation (PID)
- ✓ IEC 61701: Salt Mist Corrosion Test
- ✓ IEC 62716: Ammonia Corrosion Test
- ✓ ISO 9001: Quality Management System
- ✓ ISO 14001: Environmental Management System
- ✓ ISO 45001: Occupational Health and Safety Management Systems

*Some are under process



swelect
Stay powerful when sun shines. And thereafter...

Electrical Characteristics Bi-Facial Gain @ Different Albedo %

	RATE POWER (P Max) Wp	OPEN CIRCUIT VOLTAGE (Voc) V	MAXIMUM POWER VOLTAGE (Vmp) V	SHORT CIRCUIT CURRENT (Is) A	MAXIMUM POWER CURRENT (Imp) A	MODULE EFFICIENCY η (%)
SWT15BG8605	605	55.22	45.80	13.97	13.21	21.64
	10%	55.22	45.80	15.37	14.53	23.81
	25%	55.22	45.80	17.46	16.51	27.05
	40%	55.22	45.80	19.56	18.49	30.30
SWT15BG8610	610	55.35	45.94	14.03	13.28	21.82
	10%	55.35	45.94	15.43	14.61	24.00
	25%	55.35	45.94	17.54	16.60	27.28
	40%	55.35	45.94	19.64	18.59	30.55
SWT15BG8615	615	55.48	46.08	14.09	13.35	22.00
	10%	55.48	46.08	15.50	14.69	24.20
	25%	55.48	46.08	17.61	16.69	27.50
	40%	55.48	46.08	19.73	18.69	30.80
SWT15BG8620	620	55.61	46.22	14.15	13.43	22.18
	10%	55.61	46.22	15.57	14.77	24.40
	25%	55.61	46.22	17.69	16.79	27.73
	40%	55.61	46.22	19.81	18.80	31.05
SWT15BG8625	625	55.74	46.36	14.21	13.50	22.36
	10%	55.74	46.36	15.63	14.85	24.59
	25%	55.74	46.36	17.76	16.88	27.95
	40%	55.74	46.36	19.89	18.90	31.30
SWT15BG8630	630	55.87	46.50	14.27	13.57	22.54
	10%	55.87	46.50	15.70	14.93	24.79
	25%	55.87	46.50	17.84	16.96	28.17
	40%	55.87	46.50	19.98	19.00	31.55




TEMPERATURE RATINGS	
NOCT	45°C ±2°C
Tc of Voc	-0.216%/°C
Tc of Isc	+0.041%/°C
TC of Power	-0.291%/°C
Operating Range	-40°C to +85°C
Power Binning	-0/+4.99W

MAXIMUM RATINGS	
System Voltage	1500 V _{dc}
Fuse Rating	30 A
Application / Safety	Class A; Protection Class II Fire - C; Type 4
Snow Load	5400 Pa
Wind Load	2400 Pa
Bifaciality Factor	80±5%

CONSTRUCTION	
Cell / Matrix	N-Type Topcon Cells; 156, 2 x (13 x 6)
Dimension	2465 x 1134 x 35 mm
Weight	35.7 kg
Glass	ARC; Low Iron; Semi Tempered; High Light Transmission; 2.0 mm
Encapsulation	High Volume Resistivity and Low MVTR
Substrate	Low Iron; Semi Tempered; High Light Transmission; 2.0mm
Frame	18μ Anodized Aluminium Alloy; Twin Wall Profile
Diode	Schottky Bypass Diodes
Locking	Corner Key Type
Junction Box	IP68; Junction Box
Cable	4 mm ² ; (+ ve) 300mm, (- ve) 250mm Cable Length (Customized cable length available on request)
Connector	MC4 Compatible

PACKING CONFIGURATION		
Container	20 feet (open type)	40 feet ('HC)
Pieces per Pallet	29	29
Pallets per Container	10	20
Pieces per Container	290	464

Note: Design & Specifications are subjected to change without notice. Electrical Parameters measured at STC only (at 25°C, 1000 W / m²). Test uncertainty for Pmp ±3%. Please refer to installation manual and strictly adhere to instruction / guidelines to qualify for warranty terms.



I-V Curve of 630W at 25°C cell temp. and different irradiance level



swelectes.com



SWELECT ENERGY SYSTEMS LIMITED

SWELECT HOUSE

No 5, Sir P. S. Sivasamy Salai, Mylapore, Chennai - 600 004.
Tamil nadu, India. info@swelectes.com | +91 44 24993266

PV MODULE MANUFACTURING PLANT

SWELECT HHV SOLAR PHOTOVOLTAICS PRIVATE LIMITED

No.169,166, Sembagoundan Pudur, Kuppeplayam Village,
Coimbatore, Coimbatore North Taluk, Coimbatore District
Tamil Nadu- 641 107

SCAN QR CODE FOR
PRODUCT CATALOGS

